

Power Distribution Unit (PDU)

IEM's Power Distribution Unit's (PDU) ensure delivery of power from your critical power distribution system to the server floor or wherever the need for power may be. Our PDU's can be custom designed or utilize a standard configuration to meet specific dimensional and electrical requirements. They can include fully integrated component options from leading manufacturers.

IEM's PDU's are energy efficient and provide flexible solutions that will ultimately simplify your backup power management needs.

FEATURES & BENEFITS

- Input Voltage 600VAC, 480VAC
- Input kA rating: 65 kA at 480V and 50 kA at 600V
- Output Voltage 208Y / 120V, 415Y / 240V
- Power Rating 300 kVA, 500 kVA, 600 kVA
- Dimensions: 54"W x 42"D x 80"H
- Distribution Breakers: 6 x 400A or 8 x 250A, 35 kA rated, individually mounted
- Suitable for installation with front access only
- Control and monitoring package with 7" touch panel interface
- Revenue-grade main metering
- Transformer with electrostatic shields
- Transformer K9 or K13 rated
- Standard and custom windings, DOE2016 or CSL-3 compliant
- Multiple monitoring, alarming and SER options
- Seismic tested to worst case response spectrum
- UL & cUL Listed
- Neutral bus rated 200% rated current
- Assured selective coordination between main and branch breakers up to rated short circuit current
- Modbus TCP communications
- Standard 150 kA surge protection with EMI / RFI filtering



Power Distribution Unit (PDU)

Product Sheet
PDU Units

IEM DIFFERENCE

Fully rated bus is based on density ratings, not UL heat rise tests, resulting in more bus and lower operating temperatures.

All enclosures are designed for specific application with improved dimensional flexibility and finished using state of the art powder coating system providing an indoor finish that exceeds the 1500 hour salt spray testing requirement for outdoor equipment to 3000 hours.

Component and metering selections are based on value engineering for the application and optimized to meet specifications.

TECHNICAL SPECIFICATIONS

IEM's PDU's meet or exceed applicable industry standards, including UL891, CSA C22. 2 No. 244, NEMA standards PB-2, NEMA 1 and NEMA 3R enclosures. Uses UL489 listed breakers.

IEM's PDU's meet seismic testing, circuit requirements as outlined by IEEE693 and ICC-ES-AC156.



Industrial Electric Mfg.™ (IEM)

Headquartered in Fremont, CA, IEM is the largest independent full-line manufacturer of electrical distribution and integrated control systems in the U.S. For over half a century, IEM has delivered customer-specific solutions to meet the ever changing power requirements of growth industries in North America. At IEM, tradition and technology still drive innovation. An experienced engineering staff and one of the most flexible design and manufacturing systems in the industry set IEM apart from standard product manufacturers.



Corporate Headquarters

Industrial Electric Mfg.™
48205 Warm Springs Blvd
Fremont CA 94539 USA
dir: +1.510.656.1600

Vancouver

Industrial Electric Mfg.™
3261 192 St.
Surrey, B.C. V3Z 1A7 CAN
dir: +1.866.302.9836

Jacksonville

IEM Power Systems™
3600 Port Jacksonville Parkway
Jacksonville FL 32226 USA
dir: +1.904.365.4444

www.iemfg.com